

Go Power![®]

100AH 12V LITHIUM BATTERY



EFFICIENT HIGH-PERFORMANCE SOLAR POWER STORAGE



Model #: GP-LiFePO4-100

Features:

- Can be used with lithium compatible Go Power! solar, inverters and charge controllers
- Max Power Capacity; carries almost double the power of regular batteries
- Lightweight
- Quick charging
- Over and under voltage protection
- Over and under temperature protection
- Charge and discharge over current protection
- Short circuit protection
- Drop-in replacement for Group 31 Lead Acid or AGM batteries
- **10-year warranty**

Only suitable for 12-volt applications.

DO NOT WIRE IN SERIES.

SPECIFICATIONS

Technology	Lithium Iron Phosphate
Nominal Voltage	12.8 V
Nominal Capacity	100 Ah
Nominal Operating Temperature	77 ±5 °F (25 ±3 °C)
Maximum Charge Voltage	14.6 VAC
Maximum Discharge Current	100A (continuous); 120A (30 minutes); 150A (5 seconds)
Over-charge Protection Voltage	14.6V
Over-charge Protection Voltage of a single cell	2.1V
Maximum Temperature Protect Charge	32°F (0°C) to 131°F (55°C)
Maximum Discharge Temperature Range	-4°F (-20°C) to 131°F (55°C)
BMS Leakage Current	≤3mA
Certifications	UN 38.3; CE
Cycle Life	90% Depth of Discharge ~ 3000 cycles

MECHANICAL

Length	12.9 in / 328 mm
Width	6.5 in / 165 mm
Height	9.2 in / 233.7 mm
BCI Group #	31
Weight	36 lbs / 16.33 kg
Carrying	Nylon Strap

MATERIALS

Case and Cover	ABS
Active	LiFePO4
Venting Valve	Rubber, opening pressure 8-20kPa

Specifications may be subject to change. Product may not be exactly as shown. Specifications subject to local environmental conditions.



100AH 12V LITHIUM BATTERY

Unit Dimensions



PLEASE NOTE

Lithium batteries ship under Class 9 Dangerous Goods PI 965 Section IA, which requires special carrier instructions. Please contact your carrier company to determine their requirements for shipping.

MSDS Sheets are available upon request.